

Product Information:


Primer 961

Primer for porous surfaces

General description & application:

Primer 961 is an adhesion promoter, especially developed to improve adhesion of MS-polymer, polyurethan (PU) and silicone based sealants to porous substrates and to metals like copper and brass.



Member of  Danish Association of Sealant Applicators & Manufactures.

Physical / chemical properties:

Primer:

- Type: 1-component solution of organic silicium compounds.
- Colour: Colourless
- Consistency: Liquid
- Specific gravity: Approx. 0,9 kg/litre.
- Shelf life: Minimum 6 months in unopened packing, if stored cool and dry.
- Packaging:

Item no.	Size
7574	250 ml metal bottle
75751	1000 ml metal bottle



Directions for use:

- Preparation:* All surfaces must be clean, dry, free of grease, dust and loose particles.
- Before application of the primer, all surfaces must be degreased with f.ex. acetone or ethanol. Metal surfaces must be mechanical cleaned before degreasing.
- The choice of primer must be made after sufficient adhesion- and compatibility tests.
- Application:* Primer 961 is applied with a soft brush or cloth, in a thin even layer. Application should be made carefully, as the primer will be visible after drying. Use covering tape if necessary.
- Consumption:* 85 ml/m² adhesion surface
- Drying time:* 40 - 60 minutes at 20 °C.
- The sealant should be applied immediately after complete drying of the primer, to avoid contamination of the primed surface.
- Cleaning:* The brush can be cleaned with an organic solvent, f.ex. acetone.

Health and safety:

For further information on safety, refer to product safety data sheet.

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK
PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75